




# LT07







## 4G Magnetic Asset Tracker

The LT07 Series is a compact 4G magnetic tracker for long-term container and mobile asset management. Featuring a 2,700 mAh large-capacity battery, strong magnetic base, and multi-tech GPS+LBS+Wi-Fi positioning, it provides reliable location tracking. With light-sensing tamper detection and geo-fence alerts, it ensures secure.



### Applications



- **3-Year Battery Life**  
2,700 mAh disposable lithium-ion battery, with a once-daily reporting cycle for 3+ years.
- **Multi-Tech GPS+LBS+Wi-Fi**  
Reliable positioning solution leveraging both satellite and terrestrial technologies.
- **4G & 2G Network**  
Different versions available for multiple regions.
- **Strong Magnetic Base**  
With strong magnets for secure attachment and easy mounting on various surfaces.
- **Light-Sensing Tamper Detection**  
Automatically triggers an alert if exposed to light, preventing unauthorized removal.
- **Geo-fence Guard**  
Configurable virtual zones to provide immediate notification of boundary crossing.

### GNSS

Positioning system	GPS, LBS, Wi-Fi with AGPS	
Frequency	GPS L1: 1575.42MHZ	
Positioning accuracy	Less than 10 meters	
Tracking sensitivity	-165 dBm	
Acquisition sensitivity	Avg. cold start: -148 dBm	Avg. hot start: -159 dBm
TTFF (open sky)	Avg. cold start ≤ 35 sec	Avg. hot start ≤ 1 sec

### Cellular

Communication network	4G+2G	
Frequency	<b>LT07G (Asia):</b> FDD LTE: B1, B3, B5, B8 TDD LTE: B34, B38, B39, B40, B41 <b>LT07U (Europe &amp; Oceania):</b> FDD LTE: B1, B3, B7, B8, B20, B28 GSM/GPRS/EDGE: B3, B8 <b>LT07D (Latin America):</b> FDD LTE: B1, B2, B3, B4, B5, B7, B8, B28, B66 TDD LTE: B40 GSM/GPRS/EDGE: B2, B3, B5, B8	

### Power

Battery	2700 mAh 3.6 V disposable lithium-ion battery
---------	---

### Interface

LED indication	Cellular (Red), GNSS (Green)	
SIM	Micro-SIM	
Data storage	4G+2G ver. 16-packet offline storage capacity	4G ver. 128-packet offline storage capacity

### Physical specification

Dimensions	L64.5 x W41.5 x H30.5 mm (with magnet)	L64.5 x W41.5 x H27 mm (without magnet)
Weight	100 g (with magnet)	78 g (without magnet)

### Operating environment

Temperature	Operating temperature: -20°C ~ +70°C	Storage temperature: -40°C ~ +85°C
Operating humidity	5% ~ 95%	
IP rating	IP54	