



# NT35

## 4G/LTE-M Personal Tracker

NT35 series 4G/LTE-M personal tracker is a compact, IP65 device designed for personal safety and location monitoring. Featuring a dedicated one-press SOS button for instant alerts, it provides GPS+LBS+Wi-Fi positioning and 4G&2G network connectivity. With a rechargeable battery, BLE 5.0, and remote management.



### Applications



Personal Tracking

SOS

#### One-Press SOS Alert

A dedicated SOS button allows users to call for help instantly with a single press.



#### Multi-Tech GPS+LBS+Wi-Fi

Reliable positioning solution leveraging both satellite and terrestrial technologies.



#### 4G & 2G Network

Different versions available for multiple regions.



#### Track History Playback

Displays, records, and replays movement paths with status for full visibility.



#### Remote OTA Management

Enables remote configuration and firmware upgrades for easy maintenance.



#### IP65 Water & Dust Resistant

Rugged, reliable design for steady outdoor performance.

### GNSS

Positioning system	GPS, LBS, Wi-Fi with AGPS	
Frequency	GPS L1: 1575.42 MHz	
Positioning accuracy	5-10 m (5m CEP)	
Sensitivity	Tracking sensitivity: -162 dBm	Acquisition sensitivity: -148 dBm
TTFF (open sky)	Avg. cold start ≤ 35 sec	Avg. hot start ≤ 2 sec
Wi-Fi	2.4 GHz, used for indoors tracking	

### Cellular

Communication network	LTE-M/NB-IoT/4G Cat1 + GSM	
Frequency	<b>NT35E</b> LTE-M: B1, B2, B3, B4, B5, B8, B12, B13, B14, B18, B19, B20, B25, B26*, B27, B28, B66, B71 NB-IoT: B1, B2, B3, B4, B5, B8, B12, B13, B14, B85 (* Under Development ) GSM: 850, 900, 1800, 1900 MHz <b>NT35U (Europe &amp; Oceania)</b> LTE Cat1: B1, B3, B5, B7, B8, B20, B28      GSM: 850, 900, 1800, 1900 MHz <b>NT35D (Latin America)</b> LTE Cat1: B2, B3, B4, B5, B7, B8, B28, B66      GSM: 850, 900, 1800, 1900 MHz	

### Power

Battery	2900 mAh 3.7 V rechargeable Li-poly battery
Input voltage	3.7V DC
Operating current	Active < 60 mA

### Interface

LED indication	Cellular (Red), GNSS (Green), Power (Blue)
USB	Type-C
SIM	Micro-SIM
Bluetooth	BLE 5.0 (iBeacon & Gateway)
Data storage	2000-packet offline storage capacity

### Physical specification

Dimensions	L85 x W51 x H20 mm
Weight	95g

Certification	FCC (NT35E)
---------------	-------------